



NEWS

Wood Modification Alternative to Traditional Preservative Treated Wood

Details Published on Friday, 11 July 2014 08:34

Products that are challenging the traditional preservative treated wood markets have made some headway in high end niche markets. Heat treatments of wood and chemical modification using acetic anhydride to acetylate wood have been studied for many years and are now both commercially available. Both methods result in increased decay resistance and improved dimensional stability to different degrees. Strength properties of the wood are also affected mainly by heat treatments.

Both processes achieve a reduction in susceptibility to insect and decay attack while increasing dimensional stability by reducing changes in wood moisture content. Heat treatment is done by heating the wood to high temperature (up to 2400 C) typically in the presence of steam to prevent combustion. Acetylated wood results from the reaction of acetic anhydride with wood and the subsequent esterification of the accessible hydroxyl groups in the cell wall. Both processes result in a reduction of available (to attract water thereby increasing moisture content) hydroxyl groups within the wood.

For more on thermally modified wood products see:

<http://saydina.com/thermally-modified-hardwoods/>

<http://www.swm-wood.com/en/Thermally%20modified%20wood/ominaisuudet2>

<http://cambiawood.com/>

For more on acetylated wood products see:

<http://www.accoya.com/>

<http://www.eastman.com/Company/AcetylatedWood/Pages/Overview.aspx>

Richard P. Vlosky, Ph.D.

Director Louisiana Forest Products Development Center

Crosby Land & Resources Endowed Professor of Forest Sector Business Development

Room 227, School of Renewable Natural Resources

Louisiana State University

Baton Rouge, LA 70803

Phone (office): (225) 578-4527

Fax: (225) 578-4251

Mobile Phone: (225) 223-1931



11 July 2014



SENT TO LSU AGCENTER/LOUISIANA FOREST PRODUCTS DEVELOPMENT CENTER - FOREST SECTOR / FORESTY PRODUCTS INTEREST GROUP